

TexNov



PINTURA

Pre-colored and resurfacing primer

TexNov Pintura is a liquid coat based on 100% acrylic resins. It is available in all standard colors produced by **TexNov inc.** It has been specially developed as a primer before application of the finish coat (it coordinates the base coat color to finish coat color). It is designed for concrete and masonry surfaces, and for stucco and gypsum panels.

TexNov Pintura is also used to refresh acrylic, stucco or plaster surfaces. It also prevents efflorescence that may appear on the finished surface.

TexNov

Acrylic Coatings
Manufacturer

PINTURA

Pre-colored and resurfacing primer

1- Product Description

TexNov Pintura is a liquid coat based on 100% acrylic resins. It is available in all standard colors produced by **TexNov inc.**

Characteristics	Advantages
100% acrylic	Improves adhesion of finish coatings
Applicable using a roller or a compressor	Easy to use
Good cover	May be tinted to the desired color
Vapor permeability	Allows walls to "breathe"

2-Uses

TexNov Pintura has been specially developed as a primer before application of the finish coat (it coordinates the base coat color to finish coat color). It is designed for concrete and masonry surfaces, and for stucco and gypsum panels.

TexNov Pintura is also used to refresh acrylic, stucco or plaster surfaces. It also prevents efflorescence that may appear on the finished surface.

3-Covered area

Pail of 3.78L: 1 coat covers 160 pi² (14,5 m²)

Pail of 7L : 1 coat covers 280 pi² (25 m²)

Pail of 18.9L : 1 coat covers 800 pi² (74 m²)

The level of porosity of the substrate and the temperature can affect the area covered by the product.

4-Mix

Stir until smooth and creamy. No additives or accelerants should be added.

Adding water is not recommended as it will increase the drying time. If the drying is very short and the marks of the rollers are noted, you can add a maximum of 250 ml of water (1 cup = per pail of 18.9L)

5-Application

The application of the **TexNov Pintura** must be protected from both hot sun and bad weather. Both ambient air and surface temperature must be of 10°C (50°F) or above, and so maintained for a minimum of 24 hours.

Temporary protection: The wall must be protected against bad weather and other potential damage during the entire coat application time, and for 4 hours after application.

Surface Preparation: The area to be coated must be clean, dry, of good quality, and free from crusts, grease, oil, etc. Clean the surfaces to be coated with the corresponding products. Remove flaking and blisters that formed on painted surfaces before applying **TexNov Pintura**.

It can be applied using a brush, a roller or spray system.

Drying:

TexNov Pintura drying time depends on the air temperature and relative humidity. Under normal conditions, 21°C (70°F) ambient temperature and 55% relative humidity, **TexNov Pintura** is touch dry after 1 hour and dry enough to apply a finish coat after 2 hours.

Cleaning: Clean tools with water while it is still wet.

6-Product Storage

TexNov Pintura must be stored at a temperature ranging from 5 to 40°C (41 to 104°F) in a tightly sealed container and protected from direct sunlight. Product lifetime is of 1 year.

7-Physical Properties

Solids	50.0%
pH	9.5
Viscosity using the Brookfield RVT model, spindle No. D 10 rpm	15000cps
Density (20°C)	1.27 g/cm ³
Glass transition temperature at mi-point/Tg	+ 14° C
VOC (volatile organic compounds in g/L)	35

8-Transport conditions

Shipping Name : Not applicable.

TDG Classification : Not regulated.

Note: This product requires no special measures for International Transport

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

PRODUCT	COMPANY IDENTIFICATION
Name : Texnov Pintura Description : Colored primer that precedes the finish coat or serves to refresh an existing wall. Restriction of use : Use between 5°C and 30°C.	TexNov inc. 839 Joseph-Louis-Mathieu Sherbrooke, Québec, Canada J1R 0X3 Emergency Phone Number : 1 877 316-6388

SECTION 2 - HAZARD IDENTIFICATION

Pictograms

None

Warning statements

None

Product classification

None

Hazard statements

None

Precautionary statements
Prevention :

Wear gloves and safety glasses. Use in a well-ventilated area. Inhalation of sanding dust or grinding of the dry product may be harmful. These dusts can cause irritation to the airways and can damage organs (lungs). This product contains ingredients that are considered carcinogenic if transformed into dust.

Intervention - Consult a doctor if you feel unwell.

INGESTION : Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor. **EYES :** Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids. **Skin :** wash with soap and water. Take off immediately all contaminated clothing. **INHALATION :** If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.

Storage : Store at 5 to 30°C in a closed plastic container. Keep away from frost.

Disposal : Dispose of contents and container in accordance with local regulations.

SECTION 3 - COMPOSITION / INFORMATION ON THE COMPONENTS

Ingredient	# number	% (weight/weight)
Crystalline silica (Quartz)	14808-60-7	0.1 - 1
Titanium dioxide	13463-67-7	0.1 - 5

The crystalline silica and titanium dioxide contents of the product are considered encapsulated or embedded in the binder polymer and not bio-accessible by inhalation in normal use of the product. Based on current knowledge and applicable concentrations, there are no other ingredients in this product that are classified as hazardous by GHS and that should be reported in this section.

SECTION 4 - FIRST AIDS

Eye contact : Flush eyes with water. Consult a physician if irritation persists.

Skin contact : Soap and rinse exposed area thoroughly. Consult a physician if irritation persists.

Ingestion : Rinse mouth with water. Do not induce vomiting unless prompted by medical advice. Do not swallow anything to an unconscious person.

Inhalation : Move person to a well-ventilated area. Consult a doctor if headaches persist.

SECTION 5 - MESURE IN CASE OF FIRE

Non-flammable product, but it may splash if heated above boiling point.

Combustion product : If the product is heated to combustion, after the release of water vapor, carbon oxides will be emitted.

Use the appropriate extinguisher.

SECTION 6 - MEASURES TO BE TAKEN IN CASE OF ACCIDENTAL DISPERSION

Pick up all the dispersion with a shovel and eliminate the discards. Do not send the dispersion into the sewer, occurs can clog the piping.

SECTION 7 - HANDLING AND STORAGE

Handling safety precaution : Do not eat, smoke or drink in the work area. Wash hands after handling. Avoid contact with hands and eyes.

Storage safety conditions : Keep in a dry place away from frost and sunlight. The product may coagulate. The storage temperature is 5 to 30°C. Keep in a closed plastic container.

SECTION 8 - EXPOSURE CONTROL / PERSONAL PROTECTION

CONTROL PARAMETERS:

Occupational Exposure Limits : Sanding or grinding this product in its dry form may produce particles of titanium dioxide and crystalline silica.

Breathable dust	RSST		ACGIH TLV	
	VEMP	DIVS	TWA	STEL
Crystalline silica (Quartz)	0.1 mg/m ³	50 mg/m ³	0.025mg/m ³	Not available
Titanium dioxide	Not available	5000 mg/m ³	10mg/m ³	Not available

RSST : Regulation respecting occupational health and safety; VEMP : Weighted average exposure value

DIVS : Immediate danger to life and health; ACGIH : American Conference of Governmental Industrial Hygienists

TLV : Threshold limit value; TWA : Time-weighted average; STEL : Short-term exposure limit.

Individual protection measures

Respiratory protection : Wear appropriate respiratory protection if dusts / fumes / gases / mists / vapors / aerosols are possible above permissible limits. Use in a well ventilated place.

Eye Protection : To reduce exposure, wear safety glasses.

Hand protection : To reduce exposure, wear gloves. Wash your hands thoroughly after using the product. Do not eat, drink or smoke when handling this product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Creamy white liquid or colored as needed.

Odor : Low odor of ammonia.

Odor threshold : Not available

pH : 9-9.5.

Freezing point : 0°C

Boiling point : 100°C.

Evaporation rate : Not available.

Flammability (solid and gas) : Not applicable.

Explosive limit : Not applicable.

Vapor pressure : Not available.

Vapor density : Not available.

Relative density : 1,4.

Solubility in water : may be diluted with water.

Partition coefficient n-octanol / water : Not available.

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

Viscosity : 7000 mm²/s (converted from measurement on Brookfield).

SECTION 10 - STABILITY AND REACTIVITY

Chemical stability : This product is considered stable under recommended storage conditions.

Reactivity : Incompatible with strong oxidants and strong acids.

Possibility of hazardous reactions : This product can not polymerize.

Hazardous decomposition product : If the product is heated to combustion, there will be emission of carbon oxides.

SECTION 11 - TOXICOLOGICAL DATA

Routes of entry : This product may be absorbed through the respiratory, digestive and cutaneous routes.

Acute toxicity (calculated GHS):

Product	DL ₅₀ oral, mg/kg	DL ₅₀ cutaneous, mg/kg	CL ₅₀ , mg/L
TexNov Pintura	> 10000 (rat)	> 10000 (rabbit)	> 100 (rat)

Skin irritation : Virtually nil. An irritation of a mechanical nature is possible.

Irritation of the eyes : Not important. An irritation of a mechanical nature is possible.

Respiratory or skin sensitization : Virtually nil.

Specific target organ toxicity : Crystalline silica can cause damage to organs (liver, spleen, kidneys, and lymph node) after repeated exposure or prolonged exposure. Levels of crystalline silica in the product are too low for GSH classification has toxic for organs. Extract from the toxicological index linked to this mention : A very small proportion of silica can pass into the bloodstream in the form of silicic acid. The latter can be deposited in the liver, spleen and lymph nodes. The silicic acid is then excreted unchanged via the kidneys.

Carcinogenicity :

The sanding or grinding of this product is its dry form can produce particles of titanium dioxide and crystalline silica which are considered carcinogens classified 2B and 1 respectively according to IARC. Repeated inhalation of crystalline silica can cause lung damage and silicosis.

Ingredient	CIRC	ACGIH	NTP
Crystalline silica (Quartz)	Group 1	Group A2	K
Titanium dioxide	Group 2B	Group A4	N

CIRC : International Center for Research on Cancer. *Group 2B* : May be carcinogenic to humans. *Group A4* : Non-classifiable substance as a carcinogen to humans. *NTP* : National Toxicology Program; *N* : Negative.

Reproductive toxicity : none.

Germ cell mutagenicity : none.

SECTION 12 - ECOLOGICAL DATA

Ecotoxicology : Not available.

Bioaccumulative potential : Not available.

Volatile organic compounds (V.O.C.): ≤ 50g / L.

SECTION 13 - DATA FOR DISPOSAL OF THE PRODUCT

Dispose of releases in accordance with municipal, provincial and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Shipping Name : Not Applicable.

TDG Classification : Not Regulated.

SECTION 15 - - REGULATORY INFORMATION

WHMIS 2015 Classification : None

The product classification and the SDS have been developed in accordance with the HPR.

SECTION 16 - OTHER INFORMATION

SDS prepared by : TexNov inc.

Emergency telephone number : 1-800-688-5990

Revision Date : 2023-07-01

Warning : The information and recommendations contained in this document have been written to the best of knowledge and technical data collected by **TexNov inc.** at the time of the revision. This document is intended to inform users of the product about the precautionary measures when using the product. No warranty is given on the properties mentioned on the products. No liability will be assumed for cases of misuse of the product or failure to observe the safety instructions contained in this document.