Effective Date: 2011-01-15 - Revision Date: 2023-07-01



SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

PRODUCT	COMPANY IDENTIFICATION
Name : Texnov Magma	TexNov inc.
Description : Acrylic waterbased metallic finish coating.	839 Joseph-Louis-Mathieu
Restriction of use : Sanding or grinding the dried product emits	Sherbrooke, Québec, Canada J1R 0X3
dangerous dust.	Emergency Phone Number : 1 877 316-6388

SECTION 2 - HAZARD IDENTIFICATION

Pictograms None. Warning statements None. Product classification None. Hazard statements None. Precautionary statements

Prevention : Wear gloves and safety glasses. Use in a well-ventilated area. Inhalation of sanding dust or grinding of the dry product may be harmful. These dusts can cause irritation to the respiratory tract and can damage organs (lungs). This product contains ingredients that are considered carcinogenic if transformed into dust.

Intervention

INGESTION: Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor. EYES : Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids. SKIN : wash with soap and water. Take off immediately all contaminated clothing. INHALATION : If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.

STORAGE: Store at 5 to 30°C in a closed plastic container. Keep away from frost.

DISPOSAL: Dispose of contents and container in accordance with local regulations.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS number	% (weight/weight)
Titanium dioxide	13463-67-7	0.1 – 1

The titanium dioxide content of the product is considered encapsulated or embedded in the binder polymer and not bio-accessible by inhalation in normal use of the product. Based on current knowledge and applicable concentrations, there are no other ingredients in this product that are classified as hazardous by GHS and that should be reported in this section.

SECTION 4 - FIRST AID MEASURES

Eye contact : Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids.

Skin contact : Wash with soap and water. Take off immediately all contaminated clothing.

Ingestion : Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor.

Inhalation : If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.

The application instructions and performance characteristics are based on information we believe to be reliable.

They are offered to the best of our knowledge, but without guarantee, as conditions and methods of use of our products are beyond our control.



SECTION 5 - FIRE-FIGHTING MEASURES

Non-flammable product, but it may splash if heated above boiling point.

Combustion product : If the product is heated to combustion, after the release of water vapor, carbon oxides will be emitted. **Use the appropriate extinguisher.**

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Pick up all the dispersion with a shovel and eliminate the discards. Do not send the dispersion into the sewer, occurs can clog the piping.

SECTION 7 - HANDLING AND STORAGE

Handling safety precaution : Do not eat, smoke or drink in the work area. Wash hands after handling. Avoid contact with hands and eyes.

Storage safety conditions : Keep in a dry place away from frost and sunlight. The product may coagulate. The storage temperature is 5 to 30°C. Keep in a closed plastic container.

SECTION 8 - EXPOSURE CONTROL / PERSONAL PROTECTION

CONTROL PARAMETERS:

Occupational Exposure Limits :

Breathable dust	RSST		ACGIH TLV	
Ingredient	VEMP	DIVS	TWA	STEL
Titanium dioxide	Not available	5000 mg/m ³	10mg/m ³	Not available

RSST : Regulation respecting occupational health and safety; VEMP : Weighted average exposure value

DIVS : Immediate danger to life and health; ACGIH : American Conference of Governmental Industrial Hygienists

TLV : Threshold limit value; TWA : Time-weighted average; STEL : Short-terrm exposure limit

Individual protection measures

Respiratory protection : Wear appropriate respiratory protection if dusts / fumes / gases / mists / vapors / aerosols are possible above permissible limits. Use in a well ventilated place.

Eye Protection : To reduce exposure, wear safety glasses.

Hand protection : To reduce exposure, wear gloves. Wash your hands thoroughly after using the product. Do not eat, drink or smoke when handling this product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance : White or colored gel. Odor : Low odor of ammonia. Odor threshold : Not available pH : 8-9. Freezing point : 0° C Boiling point : 100° C. Evaporation rate : Not available. Flammability (solid and gas) : Not applicable. Explosive limit : Not applicable. Vapor pressure : Not available. Vapor density : Not available. Relative density : 1,05 - 1.1. Solubility in water : may be diluted with water.



Effective Date: 2011-01-15 - Revision Date: 2023-07-01

Partition coefficient n-octanol / water : Not available.

Auto-ignition temperature : Not applicable.

Decomposition temperature : Not available.

Viscosity: 10000 mm²/s (converted from measurement on Brookfield).

SECTION 10 - STABILITY AND REACTIVITY

Chemical stability : This product is considered stable under recommended storage conditions.

Reactivity : Incompatible with strong oxidants and strong acids.

Possibility of hazardous reactions : This product can not polymerize.

Hazardous decomposition product : If the product is heated to combustion, there will be emission of carbon oxides.

SECTION 11 - TOXICOLOGICAL INFORMATION

Routes of entry : This product may be absorbed through the respiratory, digestive and cutaneous routes. **Acute toxicity (calculated GHS):**

Product	DL ₅₀ oral, mg/kg	DL_{50} cutaneous, mg/kg	CL ₅₀ , mg/L
Texnov Magma	> 10000 (rat)	> 10000 (rabbit)	> 100 (rat)

Skin irritation : Virtually nil. An irritation of a mechanical nature is possible.

Irritation of the eyes : Not important. An irritation of a mechanical nature is possible.

Respiratory or skin sensitization : Virtually nil.

Specific target organ toxicity : None

Carcinogenicity:

The sanding or grinding of this product is its dry form can produce particles of titanium dioxide which is considered carcinogens classified 2B according to IARC.

Ingredient	CIRC	ACGIH	NTP
Titanium dioxide	Group 2B	Group A4	Ν

CIRC : International Center for Research on Cancer. Group 2B : May be carcinogenic to humans. Group A4 : Non-classifiable substance as a carcinogen to humans. NTP : National Toxicology Program; N : Negative.

Reproductive toxicity : none. Germ cell mutagenicity : none.

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicology : Not available. Bioaccumulative potential : Not available. Volatile organic compounds (V.O.C.) : \leq 130g / L.

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of releases in according to Municipal, Provincial and National Regulations.

SECTION 14 - TRANSPORT INFORMATION

Shipping Name : Not Applicable. TDG Classification : Not Regulated.



Effective Date: 2011-01-15 - Revision Date: 2023-07-01



WHMIS 2015 Classification : None.

TexNov

The product classification and SDS have been developed in accordance with the HPR.

SECTION 16 - OTHER INFORMATION

SDS prepared by : Texnov inc. Emergency telephone number : 1-877-316-6388 Revision Date : 2023-07-01

Warning : The information and recommendations contained in this document have been written to the best of knowledge and technical data collected by Texnov Inc. at the time of the revision. This document is intended to inform users of the product about the precautionary measures when using the product. No warranty is given on the properties mentioned on the products. No liability will be assumed for cases of misuse of the product or failure to observe the safety instructions contained in this document.



839 Joseph-Louis-Mathieu, Sherbrooke J1R 0X3 www.texnov.com - info@texnov.com 1 877 316-6388